

MINI Cooper & Cooper S 4-Door F65, 2025 US MY	MINI USA Corporate Communications	
	Cooper	Cooper S
<b>Basic data summary</b>		
Transmission type	automatic	automatic
Seats	5	5
Number of doors	4-door car	4-door car
Drivetrain	Front-wheel drive	Front-wheel drive
<b>Gearbox data</b>		
ICE main gearbox - type, -	automatic	automatic
ICE main gearbox - number of gears, -	7	7
Axle drive front axle - ratio, -	1	1
Total internal ratios gearbox - 4th, -	3.785	3.785
Total internal ratios gearbox - 5th, -	2.972	2.972
Total internal ratios gearbox - 3rd, -	5.456	5.456
Total internal ratios gearbox - R, -	13.441	13.441
Total internal ratios gearbox - 7th, -	1.9	1.9
Total internal ratios gearbox - 6th, -	2.345	2.345
Total internal ratios gearbox - 2nd, -	8.776	8.776
Total internal ratios gearbox - 1st, -	14.964	14.964
<b>Engine data - Internal Combustion</b>		
ICE - maximum rpm to rated power, 1/min	6500	6500
ICE - rated power (SAE) - BHP	161	201
Weight to power ratio, kg/kW	11.6	9.3
Engine torque communication - ftlbs, ftlbs	184	221
ICE - valves per cylinder	4	4
ICE - rpm(s) to rated torque, 1/min	1520 - 4400	1450 - 4500
ICE - rpm(s) to rated power, 1/min	5000 - 6500	5000 - 6500
ICE - gasoline octane number power rating, -	AKI 93	AKI 93
ICE - gasoline octane number minimum, -	AKI 87	AKI 87
ICE - gasoline octane number recommended, -	AKI 91	AKI 91
ICE - gasoline max. ethanol share, -	E15	E15
ICE - cylinders, -	4	4
ICE - compression ratio, :1	11.1	11.1
ICE - minimum rpm to rated torque, 1/min	1520	1450
ICE - maximum rpm to rated torque, 1/min	4400	4500
ICE - bore - inch, inch	3.23	3.23
ICE - stroke - inch, inch	3.72	3.72
ICE - displacement - inch <sup>3</sup> , inch	121.93	121.93
<b>Exterior</b>		
Ground clearance, curb weight (H156 OTD), mm	132	132
Vehicle width (W103 OTD) inch, inch	68.7	68.7
Minimum turning circle (D 102) ft, ft	37.4	37.4
Vehicle height (H101-M) inch, inch	57.6	57.6
Wheelbase (L101) inch, inch	101.1	101.1
Vehicle length (L103 OTD) inch, inch	158.9	158.9
Overhang rear (L105 OTD) inch, inch	27.2	27.2
Overhang front (L104 OTD) inch, inch	30.7	30.7
Vehicle width at side mirrors (W144) inch, inch	77.6	77.6
<b>Interior</b>		
Seat, Total number seats	5	5

CONFIDENTIAL

Seat, row 1 Number seats	2	2
Seat, row 2 Number seats	3	3
Head room 2.SR with sunroof (H61-2 SR) inch, inch	36.2	36.2
Head room 2.SR (H61-2) inch, inch	37.5	37.5
Head room 1.SR with sunroof (H62-1 SR) inch, inch	38.6	38.6
Head room 1.SR (H62-1) inch, inch	39.8	39.8
Elbow width 1.SR (W10-1) in inch, inch	52.8	52.8
Elbow width 1.SR (W10-2) in inch, inch	52.3	52.3
<b>Luggage volumes</b>		
Largest luggage volume behind 1.SR, l	925	925
Luggage volume behind 2.SR, l	275	275
<b>Performance</b>		
0-60 mph, s	7.7	6.5
Top speed - mph	130	130/150
<b>Chassis</b>		
track front, inch	59	59
track rear, inch	59.1	59.1
Power Steering	EPS	EPS
<b>Wheel/Tires</b>		
Standard tires (AS, non-RF)	215/45 R17	215/45 R17
Standard rims	7Jx17	7Jx17
<b>Vehicle weights - US</b>		
Vehicle curb weight US, lbs	3078	3089
GVWR, lbs	4079	4079
GAWR front axle, lbs	2304	2315
Max roof load, lbs	165	165
GAWR rear axle, lbs	2017	2006
Payload, lbs	946	941
Fuel tank capacity US (gallons)	11.6	11.6

MINI COOPER, COOPER S & JCW 2-DOOR 2025 MY US (F66)	MINI USA Corporate Communications		
	Cooper	Cooper S	JCW
<b>Basic data summary</b>			
Transmission type	automatic	automatic	automatic
Engine description	B48A20M2	B48A20M2	B48A20O2
Seats	4	4	4
Number of doors	2-door car	2-door car	2-door car
Drivetrain	Front-wheel drive	Front-wheel drive	Front-wheel drive
<b>Gearbox</b>			
ICE main gearbox - type, -	automatic	automatic	automatic
ICE main gearbox - number of gears, -	7	7	7
Axle drive front axle - ratio, -	1	1	1
Total internal ratios gearbox - 4th, -	3.785	3.785	3.968
Total internal ratios gearbox - 5th, -	2.972	2.972	3.153
Total internal ratios gearbox - 3rd, -	5.456	5.456	5.787
Total internal ratios gearbox - R, -	13.441	13.441	14.255
Total internal ratios gearbox - 7th, -	1.9	1.9	2.015
Total internal ratios gearbox - 6th, -	2.345	2.345	2.478
Total internal ratios gearbox - 2nd, -	8.776	8.776	9.307
Total internal ratios gearbox - 1st, -	14.964	14.964	15.87
<b>Engine Data - Internal Combustion</b>			
ICE - maximum rpm	6500	6500	6000
ICE - minimum rpm to rated power, 1/min	5000	5000	5000
Engine power - BHP	161	201	228
Engine torque - ftlbs	184	221	280
ICE - valves per cylinder	4	4	4
ICE - rpm(s) to rated torque, 1/min	1520 - 4400	1450 - 4500	1500 - 4000
ICE - rpm(s) to rated power, 1/min	5000 - 6500	5000 - 6500	5000 - 6000
ICE - engine code,	B48A20M2	B48A20M2	B48A20O2
ICE - gasoline octane number power rating, -	AKI 93	AKI 93	AKI 93
ICE - gasoline octane number minimum, -	AKI 87	AKI 87	AKI 87
ICE - gasoline octane number recommended, -	AKI 91	AKI 91	AKI 93
ICE - gasoline max. ethanol share, -	E15	E15	E15
ICE - compression ratio, :1	11.1	11.1	10.5
ICE - minimum rpm to rated torque, 1/min	1520	1450	1500
ICE - maximum rpm to rated torque, 1/min	4400	4500	4000
ICE - displacement, cm <sup>3</sup>	1998	1998	1998
ICE - bore - inch	3.23	3.23	3.23
ICE - stroke - inch	3.72	3.72	3.72
ICE - displacement - inch <sup>3</sup>	121.93	121.93	121.93
<b>Seating</b>			
Seat, Total number seats, -	4	4	4
Seat, row 1_ Number seats, -	2	2	2
Seat, row 2_ Number seats, -	2	2	2
<b>Exterior Data</b>			
Ground clearance, curb weight (H156 OTD), mm	130	130	130
Vehicle width (W103 OTD) inch, inch	68.7	68.7	68.7
Minimum turning circle (D 102) ft, ft	36.4	36.4	36.4
Vehicle height (H101-M) inch, inch	57.2	57.2	57.2
Wheelbase (L101) inch, inch	98.2	98.2	98.2
Vehicle length (L103 OTD) inch, inch	152.6	152.6	152.6
Overhang rear (L105 OTD) inch, inch	23.7	23.7	23.7
Overhang front (L104 OTD) inch, inch	30.7	30.7	30.7
Vehicle width at side mirrors (W144) inch, inch	77.6	77.6	77.6
<b>Interior</b>			
Head room 2.SR with sunroof (H61-2 SR) inch, inch	36.3	36.3	36.3
Head room 2.SR (H61-2) inch, inch	36.9	36.9	36.9
Head room 1.SR with sunroof (H62-1 SR) inch, inch	38.3	38.3	38.3
Head room 1.SR (H62-1) inch, inch	40.3	40.3	40.3
Elbow width 1.SR (W10-1) in inch, inch	53.7	53.7	53.7

Elbow width 1.SR (W10-2) in inch, inch	49.8	49.8	49.8
<b>Luggage volumes</b>			
EPA cargo volume, ft <sup>3</sup>	8.9	8.9	8.9
Largest luggage volume behind 1.SR , l	725	725	725
Luggage volume behind 2.SR , l	210	210	210
<b>Performance</b>			
0-60 mph, s	7.4	6.3	5.9
Top speed - mph	130	130/150	130/155
<b>Track/Tires/Wheels</b>			
track front, inch	59	59	59
track rear, inch	59	59	59
Standard Tires	215/45 R17 AS non-RF	215/45 R17 AS non-RF	205/45 R17 AS non-RF
Standard rims	7Jx17	7Jx17	7Jx17
<b>Weights</b>			
vehicle curb weight US lbs	3014	3014	3047
GVWR, lbs	3825	3825	3858
GAWR front axle, lbs	2238	2238	2260
Max roof load, lbs	165	165	165
GAWR rear axle, lbs	1797	1797	1786
Payload, lbs	785	778	783
Fuel tank capacity US gallons	11.6	11.6	11.6

MINI Cooper, Cooper S & JCW Convertibles 2025 MY (F67)	MINI USA Corporate Communications		
	Cooper	Cooper S	JCW
<b>Basic data summary</b>			
Transmission type	automatic	automatic	automatic
Engine description	B48A20M2	B48A20M2	B48A20O2
Seats	4	4	4
Number of doors	2-door convertible	2-door convertible	2-door convertible
Drivetrain	Front-wheel drive	Front-wheel drive	Front-wheel drive
<b>Gearbox data</b>			
ICE main gearbox - type, -	automatic	automatic	automatic
ICE main gearbox - number of gears, -	7	7	7
Axle drive front axle - ratio, -	1	1	1
Total internal ratios gearbox - 4th, -	3.785	3.785	3.968
Total internal ratios gearbox - 5th, -	2.972	2.972	3.153
Total internal ratios gearbox - 3rd, -	5.456	5.456	5.787
Total internal ratios gearbox - R, -	13.441	13.441	14.255
Total internal ratios gearbox - 7th, -	1.9	1.9	2.015
Total internal ratios gearbox - 6th, -	2.345	2.345	2.478
Total internal ratios gearbox - 2nd, -	8.776	8.776	9.307
Total internal ratios gearbox - 1st, -	14.964	14.964	15.87
<b>Engine Data - Internal Combustion</b>			
ICE - maximum rpm to rated power, 1/min	6500	6500	6000
ICE - minimum rpm to rated power, 1/min	5000	5000	5000
Engine power SAE - BHP	161	201	228
Engine torque, ftlbs	184	221	280
ICE - valves per cylinder	4	4	4
ICE - rpm(s) to rated torque, 1/min	1520 - 4400	1450 - 4500	1500 - 4000
ICE - rpm(s) to rated power, 1/min	5000 - 6500	5000 - 6500	5000 - 6000
ICE - engine code, -	B48A20M2	B48A20M2	B48A20O2
ICE - gasoline octane number power rating, -	AKI 93	AKI 93	AKI 93
ICE - gasoline octane number minimum, -	AKI 87	AKI 87	AKI 87
ICE - gasoline octane number recommended, -	AKI 91	AKI 91	AKI 93
ICE - gasoline max. ethanol share, -	E15	E15	E15
ICE - cylinders, -	4	4	4
ICE - compression ratio, :1	11.1	11.1	10.5
ICE - minimum rpm to rated torque, 1/min	1520	1450	1500
ICE - maximum rpm to rated torque, 1/min	4400	4500	4000
ICE - displacement, cm <sup>3</sup>	1998	1998	1998
ICE - bore - inch, inch	3.23	3.23	3.23
ICE - stroke - inch, inch	3.72	3.72	3.72
ICE - displacement - inch <sup>3</sup> , inch	121.93	121.93	121.93
<b>Seating</b>			
Seat, Total number seats, -	4	4	4
Seat, row 1_ Number seats, -	2	2	2
Seat, row 2_ Number seats, -	2	2	2
<b>Exterior Data</b>			
Ground clearance, curb weight, mm	124	124	124
Vehicle width, inch	68.7	68.7	68.7
Minimum turning circle, ft	36.4	36.4	36.4
Vehicle height, inch	56.3	56.3	56.3
Wheelbase, inch	98.2	98.2	98.2
Vehicle length, inch	152.8	152.8	152.8
Overhang rear, inch	23.9	23.9	23.9
Overhang front, inch	30.7	30.7	30.7
Vehicle width at side mirrors, inch	77.6	77.6	77.6
<b>Interior</b>			
EPA passenger volume index front (SAE), ft <sup>3</sup>	48.336	48.336	48.336
EPA passenger volume index second (SAE), ft <sup>3</sup>	28.631	28.631	28.631
Head room 2.SR (H61-2) inch, inch	39	39	39
Head room 1.SR (H62-1) inch, inch	39.8	39.8	39.8
Elbow width 1.SR (W10-1) in inch, inch	53.7	53.7	53.7
Elbow width 1.SR (W10-2) in inch, inch	43.1	43.1	43.1
<b>Luggage volumes</b>			
EPA cargo volume, ft <sup>3</sup>	5.2	5.2	5.2
Luggage volume with convertible open, l	160	160	160
<b>Performance</b>			
0-60 mph, s	7.9	6.7	6.2
Top speed - mph, mph	130	130/147	130/152
<b>Track/Wheels/Tires</b>			

Track front, inch	59	59	59
Track rear, inch	59	59	59
Standard Tires	215/45 R17 AS non-RF	215/45 R17 AS non-RF	205/45 R17 AS non-RF
Standard Rims	7Jx17	7Jx17	7Jx17
<b>Weights</b>			
vehicle curb weight US, lbs	3139	3148	3197
GVWR, lbs	3979	3979	4023
GAWR front axle, lbs	2282	2282	2315
GAWR rear axle, lbs	1896	1896	1885
Payload, lbs	785	778	802
Fuel tank capacity US, gal	11.6	11.6	11.6

MINI Countryman - 2025 MY US (U25)		
	Countryman S ALL4	JCW Countryman ALL4
<b>BASIC DATA SUMMARY</b>		
Transmission type	DCT automatic - Getrag	DCT Sport automatic - Getrag
Engine description	B48A2002	B48A20T2
Seats	5	5
Vehicle configuration/class	5-door SUV	5-door SUV
Drivetrain	All-wheel drive	All-wheel drive
<b>Gearbox</b>		
ICE main gearbox - type	DCT automatic - Getrag	DCT Sport automatic - Getrag
ICE main gearbox - number of gears	7	7
Axle drive front axle - ratio	1	1
ICE AWD transfer case - ratio	0.576	0.576
Axle drive rear axle - ratio	1.737	1.737
Total internal ratios gearbox - 1st	16.991	16.991
Total internal ratios gearbox - 2nd	9.965	10.588
Total internal ratios gearbox - 3rd	6.236	7.076
Total internal ratios gearbox - 4th	4.276	4.91
Total internal ratios gearbox - 5th	3.397	4.001
Total internal ratios gearbox - 6th	2.654	3.273
Total internal ratios gearbox - 7th	2.157	2.522
Total internal ratios gearbox - R	15.363	16.323
<b>Engine Data - Internal Combustion</b>		
ICE - maximum rpm	6500	6500
ICE - rated power - SAE hp	241 @ 4500 rpm	312 @ 5750 rpm
Engine torque - ft-lbs	295 @ 1500 rpm	295 @ 2000 rpm
ICE - valves per cylinder	4	4
Emission classification (type-certified)	SULEV30	ULEV 50
ICE - rpm(s) to rated torque, 1/min	1500 - 4000	2000 - 4500
ICE - rpm(s) to rated power, 1/min	4500 - 6500	5750 - 6500
ICE - engine code	B48A2002	B48A20T2
ICE - fuel type	Gasoline	Gasoline
ICE - gasoline octane number power rating	AKI 93	AKI 93
ICE - gasoline octane number minimum	AKI 87	AKI 87
ICE - gasoline octane number recommended	AKI 91	AKI 91
ICE - gasoline max. ethanol share	E15	E15
ICE - cylinders	4	4
ICE - compression ratio x:1	10.5	9.5
ICE - displacement, cm <sup>3</sup>	1998	1998
ICE - stroke, mm	94.6	94.6
ICE - bore, mm	82	82
ICE - bore - inch	3.23	3.23
ICE - stroke - inch	3.72	3.72
ICE - displacement - inch <sup>3</sup>	121.93	121.93
<b>Interior</b>		
Total number seats	5	5
Front row seating	2	2

Second row seating	3	3
Head room 1st seat row with sunroof, mm	1034	1034
Head room 1st seat row with sunroof, inch	40.7	40.7
Head room 2nd seat row with sunroof, mm	960	960
Head room 2nd seat row with sunroof, inch	37.8	37.8
Shoulder room 1st seat row, mm	1416	1416
Shoulder room 1st seat row, inch	55.7	55.7
Shoulder room 2nd seat row, mm	1392	1392
Shoulder room 2nd seat row, inch	54.8	54.8
Leg room 1st seat row, mm	1026	1026
Leg room 1st seat row, inch	40.4	40.4
Leg room 2nd seat row, mm	941	941
Leg room 2nd seat row, inch	37	37
Knee clearance 2nd seat row, mm	63	63
Elbow width 1st seat row, mm	1459	1459
Elbow width 2nd seat row, mm	1430	1430
Luggage volume ft <sup>3</sup> (rear seats up/down)	24.98 - 56.18	24.98 - 56.18
<b>Offroad data</b>		
Ground clearance @ curb weight, mm	203	202
Ground clearance @ curb weight, inch	8	8
Ground clearance front axle @ curb weight, mm	203	202
Ground clearance rear axle @ curb weight, mm	230	228
Departure angle @ curb weight (A106-2 OTD) °	25.5	25
Approach angle @ curb weight (A106-1 OTD) °	18.5	18.7
Ramp angle @ curb weight (A147 OTD) °	20.2	20
<b>Exterior</b>		
Minimum turning circle, m	11.6	11.8
Minimum turning clearance circle, ft	38.1	38.7
Vehicle height, mm	1657	1655
Vehicle height, inch	65.2	65.2
Vehicle width, mm	1843	1843
Vehicle width, inch	72.6	72.6
Vehicle width at side mirrors, mm	2069	2069
Vehicle width at side mirrors, inch	81.5	81.5
Wheelbase, mm	2692	2692
Wheelbase, inch	106	106
Vehicle length, mm	4444	4447
Width at driver's mirror, mm	1041	1041
Width at passenger's mirror, mm	1028	1028
Overhang rear, mm	884	884
Overhang rear, inch	34.8	34.8
Overhang front, mm	868	871
Overhang front, inch	34.2	34.3
<b>Performance</b>		
Top speed - mph	130/150	130/155
0-60 mph, s	6.2	5.2
<b>Wheel/Tires/Track</b>		
Standard tires (AS, non-RF)	225/55 R18 AS	245/45 R19 AS
Standard rims	7.5X18	8X19
track rear (inch), inch	62	62.5
track front (inch), inch	62	62.4



<b>Steering</b>		
Power-steering	EPS	EPS
Steering transmission, overall, x:1	13.5	13.5
<b>Trailer towing</b>		
trailer tongue weight, kg	158	N/A
trailer towing capacity unbraked, kg	750	N/A
trailer towing capacity braked 12% category I and II, kg	1587	N/A
gross vehicle weight with trailer 12% category I and II, kg	3832	N/A
<b>Vehicle weights - US</b>		
vehicle curb weight US - lbs	3777	3836
GAWR - rear axle - lbs	2624	2590
GVWR - lbs	4949	4960
GAWR - front axle - lbs	2524	2546
Payload - lbs	1100	1089
Max roof load - lbs	165	165
<b>Fuel Tank</b>		
Fuel tank capacity US (gallons)	14.3	14.3
MINI USA Corporate Communications, 2024 <a href="http://www.miniusanew.com">www.miniusanew.com</a>		

2025 MINI Countryman SE ALL4 - US Technical Specifications	
<b>Basic Data Summary</b>	
Vehicle Classification	Crossover
Transmission type	Automatic
Engine description	Electric
Seats	5
Number of doors	4-door
Drivetrain	All-wheel drive
<b>Gearbox data</b>	
Number of gears	1
Axle drive front axle ratio	11.19
Axle drive rear axle ratio	10.053
<b>Electrical Drive System Data</b>	
Weight to power ratio, (lbs:hp)	14.9
Engine power - BHP	308
Engine torque - ftlbs	364
Emission classification (type-certified)	ZEV
Electrical system front axle drive power - BHP	188
Electrical system rear axle drive power - BHP	188
Electrical system front axle drive torque - ftlbs	182
Electrical system rear axle drive torque -ftlbs	182
<b>High Voltage Battery</b>	
Rated voltage, V	286.3
Battery capacity (net), kWh	64.7
Battery capacity (gross), kWh	66.5
Type/Technology	Li-Ion
<b>Charging Data</b>	
Charging - Level 1	1.44kW (120V)
Charging time - Level 1 (0-100%), - hr:mm	59:30
Charging - Level 2	9.6kW (240V, 40A)
Charging time - Level 2 (0-100%), - hr:mm	8:15
maximum charging Level 2 - AC standard, kW	9.6
DC Fast Charging	500A max delivery
Charging time - DC Fast Charging (10-80%), - min	0:29
Maximum charging power - DC, kW	130
<b>Performance</b>	
Top speed - mph	112
0-60 mph, s	5.4
EPA MPGe rating - combined - miles	96
EPA MPGe rating - city - miles	99
EPA MPGe rating - highway - miles	94
Total range - full charge - miles	212
KW-hrs per 100 miles	35
<b>Exterior Dimensions</b>	
Departure angle - °	24.1
Approach angle - °	17.7

Vehicle width - inch	72.6
Vehicle width at side mirrors - inch	81.5
Minimum turning circle - ft	38.7
Vehicle height - inch	64.6
Wheelbase - inch	106
Vehicle length - inch	175
Overhang rear - inch	34.8
Overhang front - inch	34.2
Track rear - inch	62.2
Track front - inch	62.1
Ground clearance - inch	7.4
Ground clearance front axle - inch	7.4
Ground clearance rear axle - inch	7.5
<b>Interior Dimensions</b>	
Seating - 1st row	2
Seating - 2nd row	3
Leg room - 1st seat row, inch	40.4
Leg room 2nd seat row, inch	35.1
Head room 2nd seat row with sunroof, inch	37.4
Head room 1st seat row with sunroof, inch	40.7
Shoulder room 2nd seat row, inch	54.8
Shoulder room 1st seat row, inch	55.7
Luggage volume, ft <sup>3</sup>	24.83-56.18
<b>Wheels/Tires</b>	
18" AS Tire Size (f/r)	225/55 R18 102 H XL AS
18" Rim Size (f/r)	7,5Jx18 LM
19" AS Tire Size (f/r) - opt.	245/45 R19 102 H XL AS
19" Rim Size (f/r) - opt.	8Jx19 LM
Run flat tires	NO
<b>Steering</b>	
Power-steering	EPS
Steering ratio, :1	14.7
<b>Weights</b>	
Roof load, lbs	168
Vehicle curb weight US, lbs	4588
GVWR, lbs	5666
GAWR front axle, lbs	2734
GAWR rear axle, lbs	3175
Max vehicle payload, lbs	1100
<b>Trailer operation</b>	
Trailer tongue weight, lbs	264
Trailer load unbraked, lbs	1653
Gross vehicle weight with trailer 12% category I and II, lb	8311
Trailer load braked 12% category I and II - lb	2645